

## Highlights:

---

- Multi-tapping 100V line transformer
- 5" full range driver
- Steel front grill with flame retardant materials
- Steel fire protection dome

The CSF506/W is a fire-protected ceiling speaker with a 5" cone, capable of producing a power of 6 Watt. It ensures a good reproduction of speech and background music. It is fitted with a 100V line transformer with power taps for 6 Watt and 3 Watt to be used in large 100V PA systems. The speaker is equipped with a special steel fire protection dome fitted around the speaker and a steel front grill with flame-retardant materials. This provides fire protection according to the EN60849 standard. The MK2 version is painted in RAL9016, to harmonize the AUDAC ceiling speaker range we decided to bring out the CSF506/W variant in RAL9010.

## Applications:

---

- Bars & Restaurants
- Retail
- Hotels
- Corporate



## Voltage:

---



## System specifications:

---

Speaker type		Broadband
Peak power handling		20 W
Program power handling		10 W
RMS/AES power handling		6 W
Line Transformer Tappings	1	6 W / 1666 $\Omega$
	2	3 W / 3333 $\Omega$
Impedance		8 $\Omega$
Frequency	Response ( $\pm$ 3 dB)	90 Hz - 18 kHz
Sound Pressure (Max. W/1m)		90 dB
Drivers		5"

## Product Features:

---

Dimensions	180 x 127 mm ( $\emptyset$ x D)
Cut-out measurement	160 mm ( $\emptyset$ )
Weight	1.300 kg
Construction	Steel fire protection dome
Front finish	Steel with flame retardant materials

## Variants:

---

- CSF506/W - White version - RAL9010

## Shipping & Ordering:

---

Packaging

Cardboard box

