

The SP series are high efficiency sound projectors designed to provide good speech intelligibility and background music in a wide variation of applications. They are all weather-proof treated to be used indoor as well as outdoor and are perfect suited to be used in large 100V broadcast systems such as train stations or airports. They all meet the IP56 Ingress Protection standard. The SP22 is a professional humidity and weatherproof unidirectional sound projector with a high efficiency level. It features a 5" full range driver and a built-in 100V line transformer with power taps for 20 Watt, 10 Watt or 5 Watt, which can be selected by connecting the corresponding pair of the 4 core connection cable.

Applications:

- Government facilities
- Retail
- Corporate



Certification:



Voltage:



System specifications:

Rated Power		20 W
Frequency	Response (± 3 dB)	110 Hz - 15 kHz
Sensitivity (1W/1m)		93 dB
Line Transformer Tappings	1	20 W / 500 Ω
	2	10 W / 1000 Ω
	3	5 W / 2000 Ω
Drivers		5"

Product Features:

Dimensions	138 x 205 mm (Ø x D)
Weight	2.200 kg
Operating temperature	-20 °C ~ 60 °C
Construction	Aluminum
Front finish	Aluminium grill
Colours	White
Projector way	1
Connection cable length	3 m

Shipping & Ordering:

Packaging	Cardboard box
Shipping weight & volume	3.000 kg - 0.0094 Cbm