

Highlights:

- Stores up to 12 units of 19" Equipment
- Integrated ventilation grid on top
- Removable sides for easy installing & cabling
- Punched square holes for use with snap-in cage nuts
- Front in depth adjustable 19" profiles (max 370 mm)
- Loading capacity of 50 kg
- Cable entry on top & bottom (closable)
- Tempered glass door with keylock

The EPR412 is an economical wall mountable 19" rack compliant to ANSI/EIA RS-310D, DIN41491, IEC 60297 standards. The construction is made of a 1.5 mm thick steel frame with 1.0 mm thick plates and is finished with a black (RAL9004) fine structured powder coating. It stores up to 12 units of 19" equipment, comes fully assembled and can easily be mounted on the wall. The 19" mounting profile with punched square holes for use with snap-in cage nuts in combination with the printed unit measurement indicators ensure easy fitting of the equipment. The tempered glass front door is reversible and secured with a key lock which keeps the equipment accessible for authorized persons only. Other present features are removable sides and in depth adjustable 19" profiles allowing easy and flexible cabling & installation.



Product Features:

Unit height		12 HE
Max. usable depth		370 mm
Max. load		50 kg
Dimensions		540 x 617 x 444 mm (W x H x D)
Weight		18.700 kg
Colours		Black (RAL9004)
Accessories	Included	2 x key for front door
		24 x Cage nuts + screws
	Optional	KM600 - M6 Cage nuts
		KS600 - M6 x 16 mm bolt DIN7985 Black

Variants:

- EPR412/B - Black version

Architects' and Engineers' Specifications:

The rack shall be a 19" type suitable for wall mounted use which complies to ANSI/EIA RS-310D, DIN41491 and IEC60297 standards with 12 usable rackspaces. It shall have the following dimensions: height 617 mm, width 540 mm and depth 444 mm with a weight of 18.7 kg. The frame of the rack shall be constructed out of cold rolled steel with a thickness of 1.5 mm while other parts shall have a thickness

of 1.0 mm. Punched square holes for use with snap-in cage nuts shall be provided for fixation of the equipment. The finishing shall be done in a textured black powder coating (RAL9004) color. The mounting rail shall be adjustable in depth and have printed unit measurement indicators. The rack shall include a tempered glass door which is reversible in position and equipped with a wing knob key lock. The sides of the rack shall be removable and the top shall have a ventilation grid.

